

EZTRA® 002

Endless O-Rings Perfluoroelastomers
REV. 01

General Application

Temperature Range

From -5°C
To 320°C

Color

Black

Application Target

High Temperatures

Compliances

Composition – IMDS Data

CAS n°	Qty %

Note

Disclaimer

Tests performed on test slabs. Temperatures, applications and indications are meant as basic suggestions and valid for static applications with no other specific media and or conditions.

PHYSICAL AND MECHANICAL PROPERTIES

Property	Test STD	Unit	Value
Density	ISO 2781	g/cm ³	1,94 ± 0,03
Hardness	ISO 7619-1	ShA	75 ± 5
Tensile Strength	ISO 37	N/mm ²	>16
Elongation	ISO 37	%	>140
Tear resistance		N/mm	>
TR 10	ASTM D1329	°C	<-1
Brittle Point		°C	<
C. Set 70h @200°C	ISO 815-1	%	<21
C. Set 70h @300°C	ISO 815-1	%	<49

AGEING PROPERTIES

Environment	Test STD	Unit	Value
Air 70h @300°C	ASTM D573		
	Hardness Change	ShA	+1,5
	Tensile Strength	%	-35
	Elongation	%	-17
	Volume	%	
	Weight	%	-1,3
Air 70h @275°C	ASTM D573		
	Hardness Change	ShA	+1
	Tensile Strength	%	-10
	Elongation	%	+15
	Volume	%	
	Weight	%	-0,3
Fuel M15 500h @40°C	ASTM D471		
	Hardness Change	ShA	-6
	Tensile Strength	%	
	Elongation	%	
	Volume	%	+7
	Weight	%	
MEK 168h @40°C	ASTM D471		
	Hardness Change	ShA	-1
	Tensile Strength	%	
	Elongation	%	
	Volume	%	+1,5
	Weight	%	

